

CLAIMS

- Sub  
Aa
1. A method of enabling a device to be controlled in which the device is operative to perform at least one function in response to control instructions from a computer system, the method including the steps of
- 5 providing a control interface containing information relating to the device function, the control interface including coded data indicative of an identity of the control interface and of at least one reference point of the control interface;
- 10 receiving, in the computer system, indicating data from a sensing device regarding the identity of the control interface and a position of the sensing device relative to the control interface, the sensing device, when placed in an operative position relative to the control interface, sensing the indicating data using at least some of the coded data; and
- 15 effecting, in the computer system and from the indicating data, an operation relating to at least one parameter of the control instructions.
2. The method of claim 1 in which said at least one parameter relating to the control instructions is associated with at least one zone of the control interface and in which the method includes effecting, in the computer system and from the zone relative to which the sensing device is located, an operation relating to said at least one parameter.
- 20 3. The method of claim 2 which includes
- 25 receiving, in the computer system, data regarding movement of the sensing device relative to the control interface, the sensing device sensing its movement relative to the control interface using at least some of the coded data; and
- effecting, in the computer system and from said movement being at least partially within said at least one zone, an operation relating to said at least one parameter of the control instructions.

4. A method of enabling a device to be controlled in which the device is operative to perform at least one function in response to control instructions from a computer system, the method including the steps of
- 5 providing a control interface containing information relating to the device function, the control interface including coded data indicative of at least one parameter of the control instructions;
- 10 receiving, in the computer system, data from a sensing device relating to said at least one parameter and regarding movement of the sensing device relative to the control interface, the sensing device, when moved relative to the control interface, sensing the data regarding said at least one parameter using at least some of the coded data and generating the data regarding its own movement relative to the control interface; and
- 15 interpreting, in the computer system, said movement of the sensing device as it relates to said at least one parameter.
5. A method of enabling a device to be controlled in which the device is operative to perform at least one function in response to control instructions from a computer system, the method including the steps of
- 20 providing a user with a control interface including coded data indicative of an identity of the control interface;
- 25 receiving, in the computer system, data from a sensing device regarding an identity of the user and regarding the identity of the control interface, the sensing device containing the data regarding the identity of the user and sensing the data regarding the identity of the control interface using at least some of the coded data; and
- effecting, in the computer system and from the data regarding the identity of the user and the identity of the control instructions, an operation relating to at least one parameter of the control instructions.
6. The method of claim 6 which includes receiving, in the computer system, data

from the sensing device regarding movement of the sensing device relative to the control interface, the sensing device generating data regarding its own movement relative to the control interface.

- 5 7. The method of any one of claims 1, 4 or 5 in which the parameter of the control instructions is selected from the group comprising:
- selecting said device;
  - selecting said function to be performed;
  - establishing default setting for said function;
  - 10 · establishing default setting for said device;
  - registering user access to control the device function;
  - authorising user access to control the device function; and
  - issuing a command code to said device to perform said function.
- 15 8. The method according to any one of claims 1, 4 or 5 further including the step of issuing a command code to said device to perform said function in response to operation of the computer system.
9. The method of claim 8 in which the command code is issued to said device
- 20 through said sensing device.
10. The method of claim 8 in which the command code is issued to said device independently of said sensing device.
- 25 11. The method according to claim 8 in which the command code is issued to said device using wireless technology.

12. The method of any one of claims 1, 4 or 5 which includes printing the control interface on demand.
13. The method of claim 12 which includes printing the control interface on a surface of a surface-defining means and, at the same time that the control interface is printed, printing the coded data on the surface.
14. The method of claim 13 which includes printing the coded data to be substantially invisible in the visible spectrum.
- 10 15. The method of claim 1, 4, or 5 which includes retaining a retrievable record of each control interface generated, the control interface being retrievable using its identity as contained in its coded data.
- 15 16. The method of any one of claims 1, 4 or 5 which includes distributing a plurality of the control interfaces using a mixture of multicast and pointcast communications protocols.
- 20 17. The method of claim 1 or 4 in which the sensing device contains an identification means which imparts a unique identity to the sensing device and identifies it as belonging to a particular user and in which the method includes monitoring, in the computer system, said identity.
- 25 18. The method of any one of claims 1, 4 or 5 which includes providing all required information relating to the device function in the control interface to eliminate the need for a separate display device.
19. The method of any one of claims 1, 4 or 5 in which the control interface is

multiple pages and in which the method includes:  
a) a computer system for enabling at least one function of the control interface, the system including:  
i) a control interface containing information relating to the function, the interface including coded data indicative of an at least one reference point of the control interface;  
ii) a computer system incorporating control instructions for performing said function and operative to receive data from a sensing device regarding said at least one reference point of the sensing device relative to the control interface, the indicating data being indicative of the position of the sensing device relative to the control interface, the indicating data using at least some of the coded data;  
b) the system of claim 29 in which said at least one reference point is associated with at least one zone of the control interface;  
c) the system of claim 29 which includes the sensing device for movement relative to the control interface;  
d) a computer system for enabling at least one function of the control interface, the system including:  
i) a control interface containing information relating to the function, the interface including coded data indicative of at least one reference point;  
ii) a computer system incorporating said control instructions and data from a sensing device regarding said at least one reference point of the sensing device relative to the control interface;

- \_\_\_\_\_

movement of the sensing device as it relates to said at least one parameter, the sensing device, when moved relative to the control interface, sensing the data regarding said at least one parameter using at least some of the coded data and generating the data regarding its own movement relative to the control interface.

5

24. A system for enabling at least one function of a device to be controlled, the system including

a control interface including coded data indicative of an identity of the control interface; and

10

a computer system incorporating control instructions to cause said device to perform said function, and operative to receive from a sensing device data regarding an identity of the user and the identity of the control interface, and for effecting, from said received data, an operation relating to a parameter of said control instructions, the sensing device containing the data regarding the identity of the user and sensing the data

15

regarding the identity of the control interface using at least some of the coded data.

25. The system of claim 24 which includes the sensing device, the sensing device sensing its movement relative to the control interface.

20 26. The system of any one of claims 20, 23 or 24 in which the parameter of the control instructions is selected from the group comprising

- selecting said device;
- selecting said function to be performed;
- establishing default setting for said function;
- 25 · establishing default setting for said device;
- registering user access to control the device function;
- authorising user access to control the device function; and
- issuing a command code to said device to perform said function.

27. A system according to any one of claims 20, 23, or 24 in which the computer is operative to issue a command code to said device to perform said function through said sensing device.

5

28. A system according to any one of claims 20, 23, or 24 in which the computer is operative to issue a command code to said device to perform said function independently of said sensing device.

10 29. The system of claim 20 or 23 in which the sensing device contains an identification means which imparts a unique identity to the sensing device and identifies it as belonging to a particular user.

15 30. The system of any one of claims 20, 23, or 24 in which the control interface is printed on a surface of a surface-defining means and in which the system includes a printer for printing the control interface on demand.

31. The system of claim 30 in which the printer prints the coded data at the same time as printing the control interface on the surface-defining means.

20

32. The system of any one of claims 20, 23, or 24 in which the coded data is substantially invisible in the visible spectrum.

25 33. The system of claim 20 or 23 which includes a database for keeping a retrievable record of each control interface generated, each control interface being retrievable by using its identity as included in its coded data.

34. The system of claim 30 in which, to cater for a control interface printed on

multiple pages, the printer includes a binding means for binding the pages.

11/11/2011 11:11:11 AM